V100/PF














Positive display 3 glass sides

- Capacity: 100 lit.
- 2 grids 710x320 mm
- Table model
- 2 sliding doors at service side.

mm	Watt	٧	kg	m ³
1052x436xh510	260	230/1	40	0.45

DOMINANTE PLUS





Positive display 3 glass sides

- Capacity: 100 lit.
- 2 grids 710x320 mm
- Table model
- 2 sliding doors at service side.
- Top part for croissants, capacity 25 litres

mm	Watt	V	kg	m ³
1052x436xh728	260+150	230/1	42	0.55

ORIZONT 100Q



ίŅ



Positive display 3 glass sides

- Capacity: 100 lit.
- Delivered with: 2 grids 600x275 mm
- Table model
- 1 sliding door at service side
- Aluminium frame " gilded ".

mm	Watt		kg	m ³
1000x390xh515	350	230/1	54	0,45



+3° +5°

- Sliding doors at service side
- Internal lighting
- Manifactured in stainless steel AISI 304 and decorated in aluminium

















	mm	Watt	٧	kg	m³	
TR6-M	1437x396xh245	200	230/1	35	0,30	13 13 13 13 13 13
TR8-B	1789x396xh245	250	230/1	40	0,35	13 13 13 13 13 13 13 13

COLD 1200C















Refrigerated structure 5xGN 1/3 h100

- Manufactured in stainless steel, curved glass panel.
- Compressor, digital thermostat
- Evaporator in copper with pipe system placed under the basin. NB: delivered without GN containers

mm	Watt		kg	m ³
1200x380xh361	130	230/1	46	0.24

COLD 1600C

Version: - 7xGN 1/3 h100

mm	Watt	V	kg	m ³
1554x380xh361	130	230/1	60	0,32

DRY 1200C





Warming structure 5xGN 1/3 h100

- Manufactured in stainless steel, curved glass panel.
- Heating through electric resistances places inside of the basin (dry heating), perforated stainless steel bottom inside the basin to protect from all contact with the resistances.
- Thermostatic regulation

NB: delivered without GN containers



mm	Watt	V	kg	m,
1200x380xh361	1000	230/1	18	0,24

DRY 1600C

Version: - 7xGN 1/3 h100

mm	Watt	v	ke	m³
1554x380xh361	1400	230/1	23	0,32

VGH2/H











Ventilated Warm showcase 2 x GN 1/1

- Interior lighting, eluminated display in front
- Humidity control, thanks to 2 drawers, to prevent the drying out of the exposed products
- For GN trays with a maximum depth of 100 mm, or pastry plates 600x400mm
- Intermediant grid 630x400 mm, curved glass and side walls, removable (maintainability)
- Portes côté service coulissantes.
- Made in stainless steel.

NB: delivered without containers

mm	kW	V	kg	m ²
800x730xh600	1,5	230/1	53	0,56

VGH3/H











+20° +85°

Ventilated refrigeration display 3xGN 1/11

- Interior lighting, eluminated display in front
- Humidity control, thanks to 2 drawers, to prevent the drying out of the exposed products.
- 100 mm high GN containers, or patissserie plate 600x400mm
- Center grill 945x400 mm, curved front glass with removable side glass.
- Sliding back glass.
- Made in stainless steel.

NB: delivered without containers

mm	kW	V	kg	m ³
1200x730xh600	1,5	230/1	71	0,75

VGR2/R

















Ventilated Refrigerated showcase 2xGN 1/1

- Interior lighting
- Electronic thermostat, automatic defrosting
- For GN trays with a maximum depth of 100 mm, or pastry plates 600x400mm
- Intermediant grid 630x400 mm, curved glass and side walls, removable (maintainability)
- Portes côté service coulissantes.
- Made in stainless steel, delivered without containers
 NB :Livré sans bacs

mm	kW	V	kg	m ³
800x730xh600	0.42	230/1	76	0.56

VGR3/R



Ventilated refrigeration display 3xGN 1/11

- Interior lighting.
- Electronic thermostat, automatic defrost
- 100 mm high GN containers, or patissserie plate 600x400mm
- Center grill 945x400 mm, curved front glass with removable side glass.
- Sliding back glass.
- Made in stainless steel,

NB: delivered without containers

mm	kW	٧	kg	m,
1200x730xh600	0,42	230/1	92	0,75

VBE-211














- Capacity 2xGN 1/1 height 150mm
- Made of: stainless steel AISI 304 security window rounded, plexi sliding doors operators side
- The halogen lamp and lighting on the upper part, associated with the bain-marie keeps the food on temperatures level desired, respecting all hygienic rules
- Drop in: stainless steel container to be insert, fitted with edges
- Easy to clean, with drainage tap
- Bin capacity: xGN 1/1 of 3xGN 1/1, max height 150mm (delivered without bin)
- Electrical heating: warmed up trough armoured elements in stainless treated incoloy and situated under the tub, thermostatic regulator from 0° till 90° C.

mm	kW	V	ka	m ³
695x602xh680	3.5	230/1	45	0.48

MEX/RG2



Cupboards stand on wheels for showcase

- Built to be used for VBE-211
- On the service side, adjustable intermediant grid
- Cable guide
- Made in stainless steel, wheels with brakes

mm	kW	V	kg	m ³
1060x615xh1380	-	-	36	1,26

VBE-311













Hot display case, bain-marie (hot water cooker) panoramic

- Capacity 3xGN 1/1 height 150mm
- Made of: stainless steel AISI 304 security window rounded, plexi sliding doors operators side
- The halogen lamp and lighting on the upper part, associated with the bain-marie keeps the food on temperatures level desired, respecting all hygienic rules
- Drop in: stainless steel container to be insert, fitted with edges
- Easy to clean, with drainage tap
- Bin capacity: 2x GN 1/1 or 3xGN 1/1, max height 150mm (delivered without bin)
- Electrical heating: warmed up trough armoured elements in stainless treated incoloy and situated under the tub, thermostatic regulator from 0° till 90° C.

mm	kW	٧	kg	m ³
1020x602xh680	3,5	230/1	55	0,68

MEX/RG3



Cupboards stand on wheels for showcase

- Built to be used for VBE-311
- On the service side, adjustable intermediant grid
- Cable guide
- Made in stainless steel, wheels with brakes

mm	kW	٧	kg	m ³
1060x615xh1380	-	-	25	1,26